



TECHNICAL DATA		
Power supply	12 V	
Current consumption	~1.5 A FM 1 kHz	
In operation	< 5 A	
Max. current	0.5 mA	
Standby current		
Frequency ranges		
Europe	FM	87.5 – 108 MHz
	MW	522 – 1629 kHz
	LW	153 – 279 kHz
	SW	5800 – 6300 kHz
NAFTA	FM	87.7 – 107.9 MHz
	AM	530 – 1710 kHz
	WB	162.4 – 162.55 MHz
APAC / MEA	FM	87.5 – 108.0 MHz
	AM	531 – 1602 kHz
LAM	FM	87.5 – 108.0 MHz
	AM	530 – 1710 kHz
Taiwan	FM	87.7 – 107.9 MHz
	AM	531 – 1602 kHz
Phillippines	FM	87.5 – 108.0 MHz
	AM	522 – 1629 kHz
Australia / New-Zealand	FM	87.5 – 108.0 MHz
	AM	522 – 1710 kHz
Inputs	1 mV for dyn. Microphones	
1 x MIC	DVD±R, DVD±RW, Audio/Video DVD mit UDF-Dateisystem, CD-DA, CD-R, CD-RW, Video CD (VCD), Super Video CD (SVCD)   RC1, RC2, RC4, RC5, WMA, MP3	
DVD drive	USB 2.0, type mini   WMA, MP3	
USB	Audio	
AUX front		
Output power	2 x 20 W	
Display	Dot matrix   amber	
Operating temperature	-20 °C to +70 °C	
Storage temperature	-40 °C to +85 °C	
Dimensions (W x H x D)	187.6 x 58.6 x 186.0 mm	
Weight	Approx. 1,420 g	
Certification	FCC, CE, RoHS, MVSS 302, UN ECE R10	
Tested acc. to	UN ECE R118	

