

BS CI priključka omogućava prijem šifriranih kanala (npr. TV kanala koji se plaćaju). Ovim Robert Bosch GmbH izjavljuje da je proizvod DVB-T2 Tuner Gen2 u skladu sa Direktivom 2014/53/EU. Cijeli tekst EU izjave o usklađenosti dostupan je na internetskoj adresi navedenoj u nastavku. Bezbijednosne napomene koje se odnose na uređaj možete naći u uputstvu za upotrebu uređaja. Uputstvo za upotrebu i izjavu o usklađenosti uređaja možete preuzeti na internetu na www.bosch-professional-systems.com.

SR DVB-T2 Tuner Gen2 je mobilni DVB-T prijemnik za zemaljske TV programe. Korišćenjem integrisanog CI priključka omogućen je prijem šifrovanih kanala (npr. TV kanala koji se plaćaju). Robert Bosch GmbH ovim izjavljuje da je proizvod DVB-T2 Tuner Gen2 u skladu sa Direktivom 2014/53/EU. Ceo tekst EU izjave o usaglašenosti dostupan je na dole navedenoj internet adresi. Bezbednosne napomene u vezi s uređajem možete naći u uputstvu za upotrebu uređaja. Uputstvo za upotrebu i izjavu o usaglašenosti uređaja možete preuzeti na internetu na www.bosch-professional-systems.com.

TECHNICAL DATA	
Power supply	12 V / 24 V (9 – 36 V)
Current consumption In operation	12 V: 910 mA 24 V: 480 mA
Max. current	12 V: 1.2 A 24 V: 0.6 A
Standby current	< 100 µA
Antennas Power supply Impedance	max. 50 mA (5 V) per antenna 50 Ω
RF reception Wavebands	VHF: 174 – 230 MHz UHF: 470 – 690 MHz
Bandwidth	7.8 MHz
Ports HDMI Version	1.0
USB Version Supported file systems Supported storage device capacity Supported image file formats	2.0 NTFS, FAT32 1 TB .png, .jpg, .bmp
AUX	2 x Video-in 2 x Audio-in (stereo)
CI	no CI+ support
Video Transmission mode Formats Codecs File formats	DVB-T, DVB-T2 1920 x 1080 x 30p H.264/AVC, H.265, MPEG2 .mov (MPEG-4 Video/MPEG-4 AAC) .mp4 (H.264/MPEG-4 AAC) .mpg (MPEG-1 Video/MPEG-1 Layer 2 (MP2))
Resolution	NTSC: 720 x 480 x 60i PAL: 720 x 576 x 50i
Audio Formats	MPEG-1/2 Layer 1 & 2, 16 – 48 kHz, Layer 2: 32 – 384 kbps Layer 1: 32 – 448 kbps MPEG-2/4 AAC-LC, 8 – 96 kHz, 8 – 576 kbps Dolby Digital AC3 (without 32-bit support) Dolby Digital Plus (DD+, without 32-bit support)
Codecs File formats	MPEG-1/2 Layer 1 & 2, MPEG-2/4 /AAC-LC, .aac, .flac, .mp3, .wav
Operating temperature	0 °C to +65 °C
Storage temperature	-40 °C to +85 °C
Dimensions (W x H x D)	227.2 x 160.8 x 30.3 mm (without connectors)
Weight	Approx. 900 g
Certification	CE, UN ECE R10, UN ECE R118, EN 50221, UKCA

